

Dow Oil, Gas & Mining

反渗透水处理用阻垢剂



ACUMER™ 4800

陶氏(DOW)ACUMER™ 4800 是一种用于反渗透水处理和热脱盐工艺的型阻垢分散剂。对硫酸钙、硫酸钡和其他低溶解度盐类有高效的阻垢效果。ACUMER™ 4800 阻垢剂是一款无磷、可降解的无害化学品,符合严格排放环保法规。

产品特点:

- 适用于热法脱盐工艺,最高耐受温度可达 100℃以上
- 无磷、可降解, 环境友好型
- 能有效控制原水中的硫酸钙、硫酸钡等物质在反渗透膜上的结垢,不加酸条件下 LSI 可达 +3.0 尚不致结垢
- 分散性能好, 使膜清洗变得容易
- 适用于所有主要反渗透膜
- 原水 pH 值在 5-10 间均有效
- 对铁和铝氧化物有较强的耐受性
- ·符合生产饮用水及食品工业标准(ANSI/NSF60认证)
- 极佳的溶解性及稳定性

理化指标:

• 外观: 澄清透明至轻微雾状琥珀色液体

• 化学特性: 聚合物

pH值: 3.5-4.5 (5 倍浓缩液); 3.0-5.0 (标准液)密度: 1.20±0.10 (5 倍浓缩液); 1.05±0.05 (标准液)

包装规格:

20 公斤桶装

储存条件:

避免阳光直射,室内常温储存(在温度低于4℃时,可能发生结冻现象,解冻后不影响使用)

使用方法:

加药剂量是根据原水水质分析报告计算所得。在推荐的剂量范围内可有效控制反渗透系统的结垢倾向

产品安全数据信息

陶氏化学可提供该产品的产品安全数据表(MSDS)。该文件包含重要的信息,您可能需要根据这些信息来保护您的员工或客户不遭受和该产品相关的已知的健康和安全危害。您可以从陶氏化学取得MSDS。另外,陶氏化学建议您也取得其他和该产品一起使用的化学品的MSDS。

For more information, call us direct at 1-800 (new number to come) for North America or internationally at (650-new number to come).

Or call our Customer information Group at 1-800-447-4369 (U.S. and Canada) or in China at 400-889-0789. Also visit www.cleanfiltration.com or www. dowoilandgas.com

From North America		From Asia Pacific		www.dow.com
Toll-free	800-447-4369	Toll-free**	+ 800-7776-7776	
Toll call	989-832-1542	Toll call	+ 60-3-7965-5392	
Fax	989-832-1465	Toll-free fax**	+ 800-7779-7779	200 200 PM
		Toll fax	+ 60-3-7958-5598	\$26.60 E-4
From Europe, India, Afr	rica and the Middle East			636344
Toll-free*	800-3-694-6367	From Latin America		TEL SEMPLES
Toll call	+ 32-3-450-2240	Toll call	+ 55-11-5188-9000	For access using your
Toll-free for Italy	800-783-825	Fax	+ 55-11-5188-9887	smartphone
Toll-free for South Africa	800-99-5078			scan the QR code above.
Fax	+ 32-3-450-2815			

- * Toll-free from Austria, Belgium, Denmark, Finland (prefix 990), France, Germany, Hungary, Ireland, The Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, and the United Kingdom
- Sweden, Switzerland, and the United Kingdom

 ** Toll free from Korea, Japan, China, Taiwan, Hong Kong, Thailand, Malaysia, Singapore, Philippines, Australia, and New Zealand

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

 $^{^{\}text{\tiny OTM}}$ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow